

OSCAAR HOT ROD SERIES



OSCAAR Mission Statement

OSCAAR (Ontario Stock Car Association for Asphalt Racers) is a non-profit organization whose membership is made up of drivers and car owners who compete in OSCAAR-sanctioned events. The Hot Rod division was created to have a sportsman like racing environment. Membership to this class is a privilege which can be revoked at anytime by a majority vote of the members.

The following rules are locked in place till the end of the 2023 race season. OSCAAR does reserve the right to unlock and make any necessary changes to preserve the spirit of competition of the series. All paid members will be notified in writing prior to this happening.

Membership Fees

The cost of an OSCAAR membership is \$225.00 prior to November 23rd, 2019. The membership will increase to \$325.00 after that date.

General Rules

OSCAAR has implemented the following general rules that apply to all of its members, drivers, car owners, crews and officials.

1. All drivers must be registered 30 minutes prior to the scheduled drivers' meeting. Failure to do so will result in starting scratch for both heat races.
2. Drivers' meeting is mandatory. All drivers must attend the drivers' meeting with one member of their race team. *Failure to attend the drivers' meeting will result in starting all heat races from scratch position.*
3. All cars must go through tech. Tech will close 30 minutes prior to the drivers' meeting. *Any cars that have not been cleared by that time will result in starting all heat races from scratch position.*
4. All cars must come to tech and cross the scales at their proper weight requirement. If not, the car will not be cleared and the driver must re-present his car for tech. The driver must be sitting in his seat in an upright position with hands on the steering wheel to obtain the proper left side percentage weight.
5. To qualify for an OSCAAR feature event, the driver must compete in at least one heat race.
6. Rainouts: Every attempt between OSCAAR Officials and visiting Track Management will be made to re-schedule events that are rained out.
7. A driver may switch to another car, however, it must be before the cars go onto the track at the start of the feature (e.g. you may not switch if there is a crash on the opening lap).

The borrowing driver must start scratch unless he has previously qualified the borrowed car. Points will be awarded to the driver.

8. Raceceivers will be mandatory in 2020. All teams must purchase a Raceceiver directly from the supplier. Any team which does not have a working Raceceiver will be fined \$50.00.
9. All teams must have a working transponder.
10. At anytime the membership may hold a vote to revoke a membership of a driver, if that driver has demonstrated on / or off track actions that are detrimental to the Hot Rod series. Only fully paid members will be eligible to vote and the decision is final for the season.

Team Racing Rules:

1. Teams will consist of one main driver and two alternative drivers
2. The cost to register would be one normal registration cost for the 1st driver and then \$50.00 each for up to two alternate drivers. The fee for alternate drivers does not have to be paid until needed.
3. Teams who wish to use alternate drivers must have names submitted to OSCAAR no later than May 1st 2020.
4. Once the list is approved by OSCAAR there will be no changes permitted for the season.
5. Alternate drivers may only be a part of one team.
6. Alternate drivers may not own or drive another car in the division they participate in.
7. OSCAAR has the right to refuse a team member based on experience or past racing history.
8. Weekly points will be rewarded to the team and counted towards the yearly championship
9. There is no limit to the amount of times each driver can participate in a season.
10. A team cannot switch drivers one the driver for that night has registered for the event.
11. Any team found to be in violation of any of these procedures will be disqualified for the event and could face future sanctions from OSCAAR.

Qualifying Procedures

1. Each driver must register with the OSCAAR officials at least 30 minutes prior to the drivers' meeting as registration will close 30 minutes prior to the drivers meeting. If a driver fails to register they will be starting scratch for the two heat races.

2. At the time of registering each driver will draw a number, which will determine the first set of heat race line ups. For example the driver that draws number one will start pole for the first heat, number two will start pole for the second heat, number three will either start second in the first heat or pole for the third heat if required.
3. Fields of over 20 cars will automatically have three sets of qualifying heats.
4. The starting order for the second set of heats will follow the same procedure as 2018
5. Each driver will earn points in the heat races based on the OSCAAR point system.
6. The top eight point earners from the heats races, will then be lined up according to the current points standing coming into the event. For example the point leader coming into the event qualifies that team would start 8th. If there was one team not in attendance, then the top point team would start 7th
7. If a driver qualifies for the invert but their team was not in attendance the week prior they will start behind the teams that were in attendance the week before.
8. The balance of the field ninth to twenty-fourth will be lined up based on points earned during the heat races.
9. Teams that were not in attendance at the previous event will be move to the rear of the field.
10. In the event that there are more than 24 cars in attendance, then the top 18 cars will qualify through earning heat race points. The balance of the field will then have to run a "B main". The length of the B main will be 10-15 laps depending on the track. Cars will be lined up according to heat race points, starting with highest and going to lowest. The top four finishers from the B main will qualify automatically for the feature. Their starting positions will be 19th-22nd. The final two starting spots will be filled by the two highest cars in the current point standing that have yet to qualify for the feature event. At tracks ½ mile and bigger, the maximum starting field will be 26 and the same procedure will be used to determine the starting field.
11. All cars that do not qualify for the feature event will receive 25 show-up points.
12. All heat races will be ten laps in length and each feature event will be thirty laps.

Race and Restart Procedures

1. All original starts will be double-file. Drivers are to accelerate out of corner 4 as the green flag is waved. There will be NO passing of any cars before the driver crosses the start/finish line. Any car jumping the start will be penalized 2 positions for every car passed. Penalty will be assessed at the next caution or at the end of the event if there are no cautions.
2. *Complete Restart*: First lap accidents in all races will be a complete restart. All cars will be restarted in their original position except those involved in the accident, which will restart at the rear of the field. This applies in all complete restarts.
3. All restarts will be double file formation. Leader has the option of restarting inside or outside the front row. All involved cars will have to restart at the rear of the field.
4. If a driver is not restarting in an acceptable manner they will be penalized two positions at the next caution period or at the end of the race if no further cautions occur.

5. When the caution flag is waved the restart will be based on the last completed lap of racing.
6. If the caution flag is shown after the leader has taken the white flag the race will attempt one time to restart the race with a green, white, checkered finish, if a second caution flag is shown the race will finish and will be scored based on the last completed green flag lap except for those cars deemed involved which will be scored at the rear of the field.
7. If a car goes to the pits during a caution period, they will be restarted at the rear of the field. If that car is still on the lead lap he will restart ahead of all cars one or more laps down.
8. A lucky dog designation during each caution period will be awarded to the first car one lap down. In the event that car is involved in the caution, no lucky dog award will be given. The lucky dog recipient will restart at the tail end of all lead lap cars. All other cars one or more laps down will continue to restart at the tail end of the field. The same driver will only receive the lucky dog once during a heat race and twice during the feature event.
9. If a driver instigates three cautions in one feature or heat race, he will be automatically black flagged for the remainder of that race. If the yellow is brought out due to mechanical issues, it will not count against the driver. If a driver uses up his three chances, for the following event that driver will only receive two chances. If those two chances are used, the following event he will have one chance. If after the first offense, the driver goes a week without being black flagged, he will again be given three chances.
10. The Race Director may at any time deem it necessary to have single file restarts.
11. Under no circumstances will OSCAAR stop a feature event to allow refueling.
12. Red Flags: When the track is under a red flag condition, all competitors are required to stop as quickly and as safely as possible. If any competitor's car moves in the pits or on the racing surface while the red flag is displayed, automatic disqualification will result. Teams that are working on repairs prior to the red flag must stop repairs until the red flag is removed. Failure to do so will result in automatic disqualification.
13. Black/Meatball Flags: Drivers given the Black or Meatball flag(s) for mechanical concerns will be given two (2) laps to report to the pits to seek consultation regarding the flag. The tech director MUST ensure that the car is safe before re-entering the racetrack at the next caution period. Failure to do so will result in immediate disqualification, loss of any points for the event, and receiving tow money only.
14. If the black flag is given for rough driving, the driver will be disqualified from the event, will receive tow money only, and lose all points for the event. Once a driver has been given the black flag the car is no longer being scored.
15. *Ignoring* the black flag will also result in disqualification, receiving no tow money, and loss of all points for the event

Involved Cars

1. All cars involved in a caution period will restart at the rear of the field.
2. If the track is blocked by an accident and a driver is required to spin to avoid the accident, and makes no contact with any other car, that driver will get his spot back for

the restart. If contact is made with any other car then you will be deemed involved and have to restart at the rear of the field.

3. If a driver spins another car, the caution flag will be shown and both cars will be restarting at the rear of the field.
4. If you are involved in an accident and then act in retaliation, you will be disqualified automatically. Disqualification will result in loss of all money and points for this event.
5. If you are an involved car and you are required to leave the track you will be given two – three courtesy laps from the time the field is in double file for the restart, you will then be lined up at the rear of the field. If the car remains on the lead lap he will restart ahead of all cars one or more laps down
6. You cannot re-enter the track once the race has been restarted. Drivers can re-enter under the next caution period. If OSCAAR has the use of a pit road, a driver may re-enter under green conditions.

Post-Race Tech Procedures

1. Following each heat race the top three finishers are required to report to the tech area.
2. Following a feature event, the top 5 drivers must report immediately to the tech area. Under no circumstances will a driver go to their pit first. Doing so will result in an automatic disqualification and loss of any money and points for the event.
3. The OSCAAR Tech Director reserves the right to do tech procedures on any car following the feature event.
4. Any driver not co-operating with the OSCAAR Tech Director will be disqualified, resulting in loss of money and points for the event and will not be permitted to participate in any event for 1 year.

Driver/Cockpit Devices

1. Traction Control – No operator controlled, radio controlled, computer controlled or automatic traction control devices or ignition re-tarder devices.
2. NO cockpit, panhard or sway bar adjustment devices.
3. NO wedge adjuster allowed.

Conduct Rules

1. The consumption of alcohol or the use of marijuana or illegal drugs, by any driver or crew member prior to the completion of the race event will not be tolerated. Infraction of this rule will result in the automatic disqualification with no points or money being awarded for that night. Anyone caught consuming alcohol or under the influence of marijuana or using illegal drugs during an event will be fined \$500.00.
2. All drivers and crew members shall act responsibly at the track. No driver, car owner, mechanic or crew member shall subject any track official or OSCAAR official to abuse, ridicule or improper use of language. Abuse of a track or OSCAAR official considered to be offensive will result in the automatic disqualification with no points or money awarded.
3. Fighting: If a driver or another member of your crew enters a fellow competitors pit area, or on the racing surface, on pit road and starts a physical fight or has a physical

altercation with an OSCAAR official that driver or team member will be removed from the series for a period of 1 year from the date of the altercation.

4. Social Media: If an OSCAAR driver or team member goes on social media (facebook, Instagram etc) and is derogatory towards the series, OSCAAR official or team. That team will be sanctioned by OSCAAR for their actions.
5. No individuals, representatives or groups will be recognized in any discussions or dispute unless the driver is registered.
6. Any driver who demonstrates erratic or hazardous driving will start in the scratch position or when warranted be removed from competition.

Official Finish and Protest System:

1. Protest must be submitted to the race director or other OSCAAR official within 20 minutes of the official finish being posted. If the protest is received after this time it not be recognized by OSCAAR.
2. Protest must be submitted by a fully paid 2020 OSCAAR member or team driver for that night. Any protest received from other individuals will not be recognized by OSCAAR
3. For all scoring protests all attempts will be made to resolve the matter that night.
4. For technical protests all attempts will be made to resolve the matter that night.
5. For technical protests a fee of \$300.00 in cash must be presented with the protest form
6. The team that files the technical protest must also present their car to have the same inspection done as they are protesting
7. If the team being protested are found to be legal they will receive the \$300.00
8. If the team being protested is found to be illegal they will be disqualified from the event forfeiting all money and points for the event. Further sanctions from OSCAAR could be issued. The team that submitted the protest will also receive the \$300.00 protest fee back.
9. If the protesting team is found to fail technical inspection they will forfeit any monies and points for the event. The team could also face further sanctions issued by OSCAAR. The \$300.00 inspection fee would remain in OSCAAR.
10. If the inspection cannot be completed at the track, OSCAAR will do their due diligence to ensure no tampering is done to the car prior to having the inspection completed at an agreed location and time.
11. The results of all inspections will be available to all fully paid members for that division.

Points System

Heat Race Points

Order	1	2	3	4	5	6	7	8	9	10
Points	7	6	5	4	3	2	1	1	1	1

If there are more than 10 cars in a heat race, then each additional position will receive 1 point:
11th = 1 point, 12th = 1 point, etc.

Feature Race Points

Order	Points
1	60
2	57
3	56
4	55
5	54
6	53
7	52
8	51
9	50
10	49
11	48
12	47

Order	Points
13	46
14	45
15	44
16	43
17	42
18	41
19	40
20	39
21	38
22	37
23	36
24	35

If there are additional cars in the feature race then the reduction of 1 point per position would still apply: 25th = 34 points, 26th = 33 points, etc.

Bonus Points

One bonus point will be awarded to each driver who leads a lap in the feature event. One additional bonus point awarded to the driver who leads the most laps in the feature event.

Rookie Points (Feature Event)

Order	1	2	3	4	5
Points	5	4	3	2	1

Frame

*Any full **Perimeter** chassis may be used. Right and left frame rails should be an equal distance from the frame centreline, there will be a 1" tolerance allowed.

*No Offset chassis allowed.

*Stock or Tube Clip, chassis allowed. See below for weight penalties.

*Rear frame sections may have 2"x3" replacement tubing from top of kick-up rearward.

*Uni-Body cars are allowed and must have the front and rear frame rails tied together by welding 2" x 3" X .095 wall tubing sections to make the connection.

*Frame ride height must be a minimum of 5" measured with the driver out of the car.

*Minimum wheelbase is 105".

***NO AFTERMARKET OR FABRICATED STRUT CARS ALLOWED.**

Roll Cage

- *No offset cages.
- *A 4 point racing roll cage is mandatory.
- *Front hoop must attach to the main cage forward to the front frame rails.
- *Rear hoop must extend over drivers head and attach to the rear frame rails.
- *4 bars on driver's door and 3 bars on passengers door or right side door bars must at least form an "X" with top bar running from front to back.
- *A fabricated plate must be installed on the outside of the driver's door bars, minimum thickness .100".
- *A "Petty" bar recommended running from center of cage to upper right front halo.
- *Upper roof halo must be minimum 32" wide.
- *No part of the roll cage may project outside the exterior sheet metal.
- *Cage must be constructed of 1 3/4" minimum outside diameter by .095" wall thickness round steel tubing.
- **Left leg protection bar must be installed.****
- *Foot box must be constructed of a minimum 12 gauge sheet steel.
- *No square tubing, channel or angle iron will be allowed in the construction of the roll cage or bracing.

Body

- *Car must be North American, steel body, year range 1949-1974.
- *Evans Bros. Fiberglass Bodies 55 -57 Chev parts will be allowed. With this roof you MUST add a piece of 14 gauge aluminum from the centre of the cage halo over the drivers head to the left side bar and must run from the front to rear of the halo.
- *Must have chrome or steel bumpers and they must have a tether strap attached to prevent them from falling off.
- *Front bumper may have "nerf bar" welded to the top to help protect the grill area. It can be 2" wider on each side of the grill and must be 2" lower than the front edge of the hood.
- *No pickup trucks, convertibles or front wheel drive cars.
- *Body to have a minimum 4 inches of ground clearance.
- *Must have stock roof, grill, tail and the rest of the body panels can be fabricated from 22 gauge sheet **steel**, but must retain stock appearance.
- *No aluminum body panels.**
- *Fiberglass racing style hoods may be used.
- *No operational cowl induction hoods allowed. Non functioning cowl induction hoods are allowed.
- *No offset bodies allowed.
- *Aluminum side skirts are allowed along each side of the body and cannot be wider than 6".
- *Bodies must be complete at beginning of each race event.
- *Roof minimum 45 inches in height, measured 10 inches back from windshield.
- *Roof may be chopped or modified to fit the chassis but MUST retain stock appearance.
- *NO laid back windshields, No rear windows are allowed or "lead sled" type modifications.

- *The side window opening must have a minimum 13" opening.
- *Lexan Windshields are mandatory to fit complete windshield opening and must have a minimum of 2 center braces and 4 safety clips –2 at top of window and 2 at bottom of window.
- *The top 6" of windshield must be kept clear for division sponsor.
- *All cars must be neat and painted.
- *Numbers must be on both door panels and the roof in large (min. 18") letters in a colour that clearly contrasts the paint. NO suffix or prefix letters allowed. ie: 99 - good and 99X - no good!
- *Original wheel arches may be removed/trimmed for tire clearance.
- *Wheels may stick out maximum of 2" from the body and measured from the tire bulge at spindle height.
- *Fender flares may be added to cover the tread area only and must not project towards the bulge in the tire.
- *Rear spoiler allowed but may not extend beyond rear edge of rear deck panel and must follow the contour of the deck lid. Maximum 5" high by the width of rear deck.
- *Bracing of rear spoiler is allowed by using approved struts only.
- *NO side pods.
- *Rub rails allowed, maximum 2" wide steel, aluminum or Lexan that can match the tire bulge from front to back. Carriage bolts only to fasten the steel or aluminum rub rails, rivets for Lexan. No sharp edges.
- *Cars must be presentable in appearance for each race.

Driver/ Cockpit Devices

- *Traction Control – No operator controlled, radio controlled, computer controlled or automatic traction control devices or ignition retard devices.
- * No chassis or suspension adjustment devices inside cockpit.
- * Brake bias adjustment device is permitted.
- *Standard, Convex or multi panel rear view mirror is mandatory.
- *One left side mirror is allowed, no larger than 3" round and must not be any farther out the then the scrub rail.

Interior

- *Interior of car can only be constructed of minimum 22 gauge steel or aluminum.
- *All roll bars in driver's area must be padded.
- *All flammable materials are not allowed in or around the driver's area.
- *Front and rear firewalls must be complete.
- *Any holes or openings must be covered with sheet metal or aluminum.

Helmet

- *For the 2020 race season Helmets must have a snell certification of 2010 or 2015. This will be the final year for the 2010 certification. Helmets without certification sticker affixed to the inside of helmet are not acceptable for use. A full face helmet is recommended. It is highly recommended that drivers wear eye protection designed for auto racing. Helmet restraints such as Hans Device, Hutchens Device or similar will be highly recommended for all events.

Fire Suit

- *Driver's fire suit SFI3.2A/1 is mandatory. Recommended SFI3.2A/5.
- *Driver and suit must maintain clean looking appearance.
- *Fireproof gloves are mandatory.
- *Fireproof neck collar, balaclava, underwear, socks, and shoes are recommended.
- *No nylon shoes allowed.

Belts & Harness

- *A quick release SFI approved 5 point harness of no less than 3 inches in width and in good condition is mandatory.
- *Belts must have date tag attached and must not be any older than 3 years (manufacturer's date). Belts with the new SFI tag and expiry date will expire at the end of the month listed on the tag.
- *Belts must be securely fastened to the frame, cross member or roll cage with a minimum of 7/16th inch grade 8 bolts and locknuts, in such a manner that all fittings are in a direct line with the direction of the pull, as per manufacturer's instructions.
- *All belts and mounting are subject to technical inspection.

Fire Control

- *Cars must have a 2 1/2 lb. minimum fire extinguisher with either steel or aluminum head and mounted in a steel bracket and must be bolted down within the driver's reach with seat belts fastened. No plastic parts are allowed on the control and discharge device.
- *On Board fire extinguisher is acceptable and must be a 5lb bottle and to have 2 nozzles in the cockpit area.
- *Fire extinguisher must be new or serviced and inspected each year and dated no later than January 1st of the current year.

Radios

- *Teams will be permitted to have radio communication with 1 spotter. Other team members cannot use a scanner. If a team is found to have additional communication through radio / scanner contact with any additional crews / family members / friends etc. They will be disqualified from the event. Teams must ensure that their raceceiver works in conjunction with the radio. Radios are not mandatory for a team to use.

Seat

- *Aluminum racing seat mandatory
- *Seat must be bolted securely with minimum diameter of 3/8 inches or larger with large steel plate washers in 4 points attached to the roll bar or frame only.
- *Full upper body head and shoulder containment seat is highly recommended.

Window Net

- *An approved nylon mesh net is mandatory, installed in driver's side window opening.
- *Window net anchors must be attached to the roll bars, not to the body.

- *Window nets must be quick release type.
- *Window net must be permanently anchored at the bottom and release at the top.

Front Suspension

- *Spring diameter 5" minimum, must be conventional coil springs only.
- ***One** Lower control arms can modified + or – 1" from stock length.
- *Load bolts allowed.
- *Spindles must be Impala style, Oldsmobile 2 piece or Howe cast only with welded steering arm.
- *Any sway bar is allowed.

Shocks

- *Steel body racing shocks only, non re-buildable.
- *Preferred shock is PRO WB Series Single Valve.
- *AFCO Series 10, 12, or 14.

Steering

- *Stock appearing steel steering box.
- *Steel Rod/Heim ends allowed – minimum 5/8".
- *Adjustable centre link allowed.
- *Steering rod to steering box must have collapsible shaft or multiple u-joints.
- *Any bolts in steering must be minimum grade 8 bolt.
- *Steering wheel must be mounted with a quick disconnect hub and have centre padding.
- *NO RACK AND PINION STEERING.

Hubs

- *5 x 5 hubs only
- *Must use 5/8" wheel studs.

Rear Suspension

- *3 link, 4 link or leaf springs allowed.
- *Trailing arms and upper link maximum 30".
- *Solid steel 3rd link with heim joints no absorbers.
- *Spring diameter to be 5" minimum conventional coil springs only.
- *4 link allowed adjustable upper arms +/- 1". Rear upper control arms can be manufactured (1"x 2" or 2"x 2") steel tubing or adjustable steel rods with minimum 5/8" steel heims no longer than stock length.
- ***TRUCK ARMS ARE ALLOWED.**
- ***NO BIRD CAGES**

Rear Ends

- *FORD 9" Rear ends with drum or disc brakes allowed.
- *FORD 9" Full floaters allowed.
- *DODGE 8 3/4" Rear ends allowed.

- *GM 12 Bolt Rear ends allowed.
- *Quick Change rear ends allowed and must have a 10" ring gear, no thermal coatings, steel tubes only.
- *RACING AXLES ARE MANDATORY.**
- *No aluminum tubes.
- *Full spool or mini spool only - No Gold Tracs, limited slip devices or post units.
- *No cambered rear ends.**

Brakes

- *All four wheels must have working brakes.
- *Rotors are to be magnetic steel only and no drilling of rotors.
- *Front rotors are minimum 1 inch thick and rear minimum are 0.750 inch thick.
- *Brake calipers must be magnetic steel with single piston.

Ignition

- *Car must be self-starting.
- *Ignition on/off switch must be mounted to the right side dash of the car and clearly labelled so that the ignition can be turned off from outside of the car in the event of an emergency.
- *The only switches allowed are: a) Master on/off mounted in the center of the car. b) Push button start switch. c) Ignition power, and off. d) Fan switch if equipped with an electric fan.
- *Stock type distributor, a DUI, or MSD distributor allowed.
- *Only 1 MSD box, one coil, and one wiring harness per vehicle.
- *MSD Blaster 2 or SS coils allowed.
- *ALL MSD WIRING TO REMAIN OPEN FOR INSPECTION. ALL WIRING MUST USE WEATHER PAK CONNECTOR 6 AND 2 PIN AT THE MSD MODULE, 2 PIN AT THE DISTRIBUTOR. MALE CONNECTORS ARE REQUIRED ON THE BOX AND DISTRIBUTOR. A 4 PIN CONNECTOR IS REQUIRED AND MUST BE ACCESSIBLE ON THE REAR OF THE TACHOMETER.
- *An operational rev chip must be accessible through the passenger window.
- *Soft touch rev control part 8728 must be mounted on the right hand side of the dash (same as ignition box) if a stock distributor and stock module are used.
- *All built engine cars will have an operational 6800 rev chip installed.
- *All crate engines will have an operational 6400 rev chip installed.
- *All 6AL, 6ALN wiring to be standard:
 - *Red wire/ignition switch
 - *Use a brown wire/tach output
 - *Black wire/coil negative
 - *Orange wire/coil positive
 - *Green wire/dist. Negative
 - *Purple wire/dist. Positive

*Connectors to be within 12 inches of the 6AL or 6ALN box. *Battery pos. and neg. May be hard wired to master disconnect and chassis ground.

MSD6CT ignition box is not allowed because of its feature that allows quick resetting.

****Anyone caught tampering with chips or rev limiter will be automatically disqualified.**

Battery

- *One 12 volt Battery only, AMG type batteries preferred.
- *Battery must be anchored securely and outside of the driver's compartment by a firewall, located ahead of the rear end, no lower than the bottom of the frame rail and in between the frame rails.
- *A battery disconnect switch is mandatory and should be located on the left side of the rear tail panel within reach of track official or safety crew member and clearly marked on and off.

Weight Location

- *Weight must be securely fastened to the chassis and mounted no lower than frame rails.
- *No weight to be added rearward of fuel cell.
- *All added weight must be **painted white** and clearly **identified with car number** on each piece.

Wheels & Tires

- *15 inch diameter steel racing wheels with a maximum width of 8" to 10" measured from bead seat to bead seat.
- *Tires for 2020- Only USED AMERICAN RACER TIRES obtained from OSCAAR Mod teams, APC teams or from Grisdale Racing Ltd are permitted. All tires used in competition must have a maximum 5/32" tread depth.
- *Teams will have a choice of using the following compounds E21 or EC31 for the 2020 season
- * Teams are able to run any combination that they wish
- * Teams found to have purchased new tires from a team or the supplier will be banned from the series for a period of one year
- * Teams found to have used any sort of tire softner will be banned for a period of one year. OSCAAR durometer readings will be final in making all decisions
- * For the dirt race at Brighton Speedway, teams are allowed a maximum of a 8 inch dirt tire, or pavement treaded tire. Teams can use the slicks as well.

Track Width

- *Wheel track width will be a maximum of 80 inches measured from outside of tire bulge at spindle height.

Engine Height

- *Engine height will be a minimum of 12 inches measured from ground to center of crankshaft.
- *Engine Location: # 1 Spark plug of engine must be in line or ahead of upper ball joint and centred in the frame. Crossmember may be altered to achieve this.

Crate Engine Options

- ***It is your responsibility to make sure your crate engine has been properly sealed and follows OSCAAR's rules.**
- *Approved crate engine is Chevrolet 350/350hp Circle Track Crate Engine Part "602".
- *No changes, substitutions or modifications to engine.

***ALL NEW CRATE ENGINES MUST BE SEALED USING 3 SEALS, ONE ON EACH SIDE OF THE INTAKE AND ONE ON THE TIMING COVER. ONLY OSCAAR APPROVED SEALS ARE ALLOWED.**

*You are allowed to replace the oil pan, pick up tube and timing chain.

*Metric Clip cars can use CANTON PAN 11-122T with CANTON 20-042 pick up tube.

*Tube Clip cars can use CHAMP PAN CP100LTRB with CHAMP 1012SB pick up tube.

*Timing Chains can be replaced with CLOYES 9-1100 double roller chain and gear set, or equivalent.

*In order to qualify for the OSCAAR crate engine program the new engine needs to be shipped directly from the dealership to one of the 2 approved engine builders or you must have a representative from OSCAAR pick up the engine with you and deliver it to one of the 2 approved engine builders. Engine builders info is listed at the back of the rule book.

*Any tampering, alterations, or violations with respect to the crate engine program will result in the immediate suspension of the driver, car owner, and chief mechanic for a minimum of 1 year (365 days) from the date of the infraction.

*Further monetary fines and reduction of points will be assessed by the technical committee.

*The tampered engine which must be removed at the team's expense will be impounded at both the team's expense and risk until the ruling is finalized.

***OSCAAR reserves the right to destroy all tampered-with parts.**

*If an OSCAAR sealed crate engine is damaged or fails, and needs to be repaired it must go to either one of the approved OSCAAR HOT ROD Series engine specialists so the repairs are made to the crate spec and then re-sealed.

* ANY Crate Engine that has been rebuilt by one of OSCAAR's approved rebuilders will need to add 75 lbs. to the total weight of the car. The rebuilt engine must be rebuilt to the specifications in the GM Circle Track Crate Engine Technical Manual.

Built Engine Definition:

*Parts available from your local dealer through ordinary parts catalogue may be accepted as stock.

*Parts ordered through dealer performance catalogues will not necessarily be considered legal.

Engine Maximum Overbore Displacement

*CHEVROLET –305-350 060 360 cu. In.

*DODGE –318-360 060 371 cu. In.

*FORD –351 (Windsor only) 060 362 cu. In. Cylinder Block Assembly (Short Block)

*Steel Block only, aftermarket engine blocks not permitted.

*The engine block must retain all factory engine dimensions, with the exception of the maximum overbore and the surfacing of the engine block deck.

*Must maintain stock lifter bore: Dodge .904 inch, Chevrolet .842 inches. Repair sleeving of lifter bores permitted to a maximum of 4.

*Crankshaft must be stock OEM-type and must have factory I.D. numbers that are legible

*Oil pan must have 1" removable plug in left front to inspect crankshaft part number

***No lightening or knife edging of crankshaft**

- *Connecting rods must be magnetic steel only.
- *Stock type, flat top or dished three ring pistons with all rings installed.
- *Compression ratio on all makes 9.5:1 or lower.

However, due to measuring variations with the equipment, a whistle of 9.9:1 will be deemed legal. If on an engine teardown, the engine exceeds 9.5:1 compression, based on exact measurements performed, the engine will be declared illegal.

Cylinder Heads

- *Cast iron OEM heads only, must be stock valve angle for manufacturer.
- *VORTEC heads are allowed only on a GM 88958602 engine.
- *DART 10021070 heads are allowed.
- *No angle plug heads will be allowed.
- *NO acid dipping, angle milling, polishing, porting or port matching of heads to intake or exhaust. **NO** hollow, sodium or titanium valves allowed.
- *Valves stem size 11/32 inch on Ford and Chevrolet heads. Chrysler heads must use 3/8" valve stems. Valves 1.94 intake and 1.6 exhaust.
- *CHRYSLER MAGNUM heads are allowed.
- *FORD may use DART 13311181 heads.
- *Ford and Chrysler must use OEM stock valve stem size.
- *All Dodge and Ford heads must be approved by Tech.
- *Must use OEM type valve springs and retainers.
- *Maximum spring diameter must be stock size for the engine used.
- *Roller rockers and stud girdles allowed.
- *Screw in studs or pinning of studs is allowed.

Camshaft

- *Flat tappet hydraulic valve lifters and camshaft only.
- *Roller rockers and stud girdles allowed. Screw in studs or pinning of studs is allowed.
- *Guide plates allowed.
- *Shaft rockers allowed on Chrysler - factory type only
- ***NO** roller or mushroom lifters.
- ***NO** aluminum, ceramic, titanium or exotic metals allowed.

Intake Manifold

- *Manifold must remain stock and unaltered as produced by manufacturer.
- *Water crossover cooling lines allowed.
- ***NO** acid dipping, grinding, porting, port matching, turtles or modifications allowed.
- *Chevrolet engines –Part #2101 (newer style only) or 2701 Vortec Performer Part #2116, Edelbrock Performer intake only.
- *Ford engines –Part #2665, 2750 or 2181 Edelbrock Performer intake.
- *Dodge engines –Part #2176, Edelbrock Performer intake or Mopar part #P4876335.

Oil Pan and Lubrication

- *Magnetic steel oil pans only.
- *Wet sump systems only.
- ***NO** external oil pump(s) (aftermarket) or external reservoir tanks allowed.

Carburetor

- *One stock 4412 –500CFM old style, metering block numbers 5924, 5925 &10570 Holley factory produced 2 barrel carburetor.
- *Only changes allowed are jets, power valve, removal of choke parts and filling in of choke rod holes.
- *Two throttle return springs and stop are mandatory.
- *May use 1" spacer.
- *No venturies in or below the spacer
- *Distance from bottom of carburetor to top of intake manifold where carburetor sits, to measure no taller than 1 1/4"including gaskets.
- *Must have air cleaner, maximum 16" x 5"
- *Air cleaner base must attach directly to carb, no spacers or hats

Cooling System

- ***NO ANTIFREEZE** allowed in the cooling system.
- *Mechanical fans must be shrouded for protection.
- *Must have overflow container or surge tank – recommended to have surge pressure blow off tube located at right side of windshield in sight of driver
- *No electric water pumps allowed.

Driveshaft

- *Drive shaft must be steel.
- *Drive shaft must be painted white.
- *Steel 360 degree retainer hoops, a minimum of 1/4 inch thick x 2 inches wide, must be positioned at the front and rear of shaft within 12 inches of each U-joint.

Exhaust System

- *Headers allowed.
- *Maximum 1 3/4" diameter tubing from header flange to collector and the maximum size of the collector 3 1/2"
- *Exhaust system must either exit outside of body and to be turned either downward and out OR exit under car on right side and behind driver and turned downward.
- *Mufflers are mandatory.
- *Muffler(s) used must remain unaltered and must meet track decibel reading.

Fuel Line

*A single AN-8 (1/2 inch) steel, armored or Kevlar braided fuel line is mandatory, and must be securely fastened under floor.

***NO NEOPRENE OR COPPER LINES allowed.**

***NO PLASTIC OR GLASS FUEL FILTERS.**

****If fuel line runs through interior of car (cab), it must run through a steel tube painted either red or yellow and marked "FUEL LINE" in contrast to your car interior.**

Fuel Pump

*Stock type mechanical fuel pump only.

Fuel Cell

*Maximum 22 U.S. gallons allowed.

*The fuel cell must be separated from the driver's compartment by an all metal firewall.

*Fuel cell is to be securely mounted in the trunk area centered between the frame rails and no lower than the centre line of the rear axel.

*Minimum of two straps to secure fuel cell (straps must be steel and a minimum of 1"x 1/8" flat strap or equivalent).

*A minimum of 20 gauge steel is to be used for fuel cell case.

*Must have a rear hoop bar for protection.

*If no vent line, cap must have a check valve.

*Fuel cell cap must be tethered to the car.

***There must be a fuel shut-off valve in working order and clearly marked ON and OFF, mounted on the right side tin kit or dash and accessible by track or safety officials.**

Transmission (Manual)

*OEM Transmission only - must be 3 or 4 speed cast iron only.

*Must have reverse gear and all forward gears must be operational.

***Transmission must be unaltered and as produced by the OEM manufacturer.**

Clutch and Flywheel

*Stock O.E.M. type friction disc minimum diameter to be 10".

*Steel pressure plates only allowed.

*Stock style clutch disc, but can be solid racing disc.

*Total clutch weight to be determined (24 lbs).

*Flywheel must not weigh less than 13 pounds.

*Only steel ring gears.

Bellhousing

*Steel bellhousing only.

*Starter mounting position must remain stock (same as on standard production bellhousing).

*Inspection hole must be in the bellhousing and be large enough to permit inspection of flywheel and pressure plate.

Transmission (Auto)

- *Automatic 2 or 3 speed transmissions and may be strengthened.
- *Modifications to shifting patterns are permitted, provided full shift pattern is retained. Scatter shield is highly recommended with automatic transmission.
- *Stock-type 10" working torque with a minimum weight of 25 lbs wet.
- *Stall test will be conducted in both forward and reverse gears.
- *Transmission oil coolers are mandatory but must not be mounted inside driver's compartment and must be contained inside the body of the car.

Weight

- *55% left side weight for cars with 108 inch wheel base 54% for cars under 108 inch
- *50% rear weight for all cars.
- *No topping up with fuel after the feature.
- *When adding ballast, a) it must be in blocks of no less than 5 pounds. b) bolted securely, painted white, to have car number painted on them. c) must have a minimum of 5" ground clearance and be secured with minimum two 1/2" bolts.
- *3 or 4 link with Crate engine and driver will be 3050 lbs.
- *3 or 4 Link cars with built engine will be 3125lbs
- *Leaf Spring cars with Crate engine will be 3100lbs
- *Leaf Spring cars with built engine will be 3175lbs
- *Tube Chassis 3 or 4 link cars with Crate engine will be 3175lbs
- *Tube Chassis 3 or 4 link cars with built engine will be 3250lbs

OSCAAR HOT ROD SERIES CRATE ENGINE SPECIALIST

Bill Howard, Howard Race Engines, 36 Ellen St., Barrie, ON. 705-721-7518

Hal Norry, Engines from Hal, 126 Malcolm Rd. Unit 5, Guelph, ON. 519-767-1532

Leitch Performance Engines 4080 North Service Road, Unit 21 Windsor, Ontario N8W 5X2 519 988-0037

These 3 engines builder will be the only accepted shops to seal the crate engines for this division. Any other seals from any other source will not be recognized and will need to meet the built engine specifications. All engine repairs are to made following the guidelines in the GM Crate Performance Manual.